



SILICONE-BASED SILKY MATT Thoroughly Wipeable, Silicone-based Interior

PRODUCT DESCRIPTION

It is a water-based, acrylic copolymer emulsion-based, silicone added silky matt top coat interior wall paint with wash it or wipe it feature that is only available in Adolin products.

PRODUCT FEATURES

Flexible structure	Resistant to scratch and impact
Thoroughly wipeable	Long lasting
Excellent adhesion	Easy application
High coverage	

AREA OF USE

Thanks to wash it or wipe it feature, it can be safely used in places that are prone to be dirty, such as apartment entrances and stairwells, offices, waiting rooms, as well as on interior parts of buildings.

APPLICATION

Surface Preparation: All kinds of dirt, oil, dust and loose material should be removed from the application surface, and places that require repairing should be repaired. Previously painted surfaces or surfaces with wallpaper should be primed with the Transition transfer primer, the surfaces with high dust emission character should be primed with Adobinder or Plaster Putty Surface Primer, dark colored or repaired surfaces should be primed with Silicone-based Universal Primer and let dry for a minimum of 8 hours.

Application: Silicone-based Silky Matt interior wall paint should be thinned 15-20% by volume and applied in 2 coats using a brush or roller. Interval between coats must be minimum 6 hours.

It should be made sure that the temperature of the application environment is higher than 5°C.

TECHNICAL SPECIFICATIONS

Resin type	Pure Acrylic	Drying Times (at 23 ± 2°C and 50% relative humidity)	
Color	Colors of the color card	Touch Dry	
Gloss	Silky Matt	Dust dry	1-2 hour
Viscosity cPoises at 25°C	350 ± 25	Recoating time	4-5 hour
Density (g/cm ³ , 20°C)	1,30 ± 5	Hard dry	6 hour
Solid Matter	55 ± 2 g/cm		12-24 hours

PAINTED AREA - CONSUMPTION

In two coats, depending on the surface;
20-25 m² surface can be painted with 2.5 Liter.
60-70 m² surface can be painted with 7.5 Liter.
130-140 m² surface can be painted with 15 Liter.

Consumption: 140-160 g/m², 125-142 ml/m²

*The specified values apply to the surfaces saturated by applying Adobinder 1/9 concentrate primer on plaster surface, and a controlled sample run should be performed to estimate the precise consumption.

STORAGE AND PACKAGING INFORMATION

Packaging Information: 2.5 Liter, 7.5 Liter, 12 Liter, 15 Liter

Storage Conditions: It can be stored for 3 years in its unopened package in a cool and dry environment at a temperature of 5 to 35°C, protecting from frost and direct sunlight.

HEALTH AND SAFETY INFORMATION

Pay attention to the health and safety statements on the product packaging. The rules specified in the product safety data sheet must be observed. Contact your nearest health care provider in case of unexpected health problems.

TSE CLASSIFICATION

Complies with TS 5808. TSE Certified.