



LATEX CEILING

PRODUCT DESCRIPTION

It is a white, matt interior surface paint specially developed for ceilings.

PRODUCT FEATURES

Good covering power	Crack-free
High whiteness	High covering capacity
Easy application	Does not splash
Breathable	

AREA OF USE

It can be easily used on ceilings, optionally on the interior parts of the buildings, on surfaces such as concrete, plaster, chip-board.

APPLICATION

Surface Preparation:

All kinds of dirt, oil, dust and loose material should be removed from the application surface, and places that require repairing should be repaired. The surfaces with high dust emission character should be primed with Adobinder 1/9 concentrate primer.

Application:

Latex Ceiling paint should be thinned 15% by weight and applied in 2 coats with 2-hour intervals.

TECHNICAL SPECIFICATIONS

Resin type	Acrylic copolymer	Drying Times (at 23 ± 2°C and 50% relative humidity)	
Color	White	Touch Dry	1-2 hour
Gloss	Matt	Dust dry	1-2 hour
Viscosity cPoises at 25°C	350 ± 25	Recoating time	1,2 hour
Density (g/cm ³ , 20°C)	1,78 ± 0.05	Hard dry	7-8 hours
Solid Matter	69 ± 2 g/cm		

PAINTED AREA - CONSUMPTION

In a single coat, depending on the type of wood; 5-6 m ² surface can be painted with 1 Kg. 18 m ² surface can be painted with 3.5 Kg. 50 m ² surface can be painted with 10 Kg.	90 m ² surface can be painted with 17.5 Kg.
---	--

STORAGE AND PACKAGING INFORMATION

Packaging Information: 3.5 Kg (1.98 L), 10 Kg (5.66 L), 17.5 Kg (9.9 L), 20 Kg (11.3 L)

Storage Conditions: It can be stored for 3 years in its unopened package in a cool and dry environment at a temperature of 5 to 35°C, protecting from frost and direct sunlight.

HEALTH AND SAFETY INFORMATION

Pay attention to the health and safety statements on the product packaging. The rules specified in the product safety data sheet must be observed. Contact your nearest health care provider in case of unexpected health problems.