



## LUX PLASTIC Interior Paint

### PRODUCT DESCRIPTION

It is a water-based, acrylic copolymer emulsion-based, silky matt top coat interior wall paint.

### PRODUCT FEATURES

High coverage  
Long lasting  
Easy application  
Breathable

Wipeable

### AREA OF USE

It can be applied on surfaces such as plaster, concrete, chipboard and briquette in exhibition stand applications and indoors.

### APPLICATION

**Surface Preparation:** All kinds of dirt, oil, dust and loose material should be removed from the application surface, and places that require repairing should be repaired. Previously painted surfaces or surfaces with wallpaper should be primed with the Transition transfer primer, the surfaces with high dust emission character should be primed with Adobinder or Plaster Putty Surface Primer, dark colored or repaired surfaces should be primed with Silicone-based Universal Primer and let dry for a minimum of 8 hours.

#### Application:

Lux Plastic interior wall paint should be thinned 15-20% by volume and applied in 2 coats using a brush or roller. Interval between coats must be minimum 4 hours. It should be made sure that the temperature of the application environment is higher than 5°C.

### TECHNICAL SPECIFICATIONS

Resin type	Acrylic copolymer	<b>Drying Times (at 23 ± 2°C and 50% relative humidity)</b>	
Color	Black, White, Red	Touch Dry	1-2 hours
Gloss	Silky Matt	Dust dry	4-5 hours
Viscosity (cPois at 25°C)	350 ± 25	Recoating time	6 hours
Density (g/cm <sup>3</sup> , 20°C)	1,50 ± 0.05	Hard dry	12-24 hours
Solid Matter	60 ± 3 g/cm		

### PAINTED AREA - CONSUMPTION

In two coats, depending on the surface;  
7-8 m<sup>2</sup> surface can be painted with 0.75 Liter.  
20-25 m<sup>2</sup> surface can be painted with 2.5 Liter.  
55-60 m<sup>2</sup> surface can be painted with 7.5 Liter.

120-130 m<sup>2</sup> surface can be painted with 15 Liter.

\*The specified values apply to the surfaces saturated by applying Adobinder 1/9 concentrate primer on plaster surface, and a controlled sample run should be performed to estimate the precise consumption.

### STORAGE AND PACKAGING INFORMATION

Packaging Information: 0.75 Liter, 2.5 Liter, 7.5 Liter, 15 Liter

Storage Conditions: It can be stored for 3 years in its unopened package in a cool and dry environment at a temperature of 5 to 35°C, protecting from frost and direct sunlight.

### HEALTH AND SAFETY INFORMATION

Pay attention to the health and safety statements on the product packaging. The rules specified in the product safety data sheet must be observed. Contact your nearest health care provider in case of unexpected health problems.

### TSE CLASSIFICATION

Complies with TS 5808. TSE Certified.