



INTERIOR PUTTY

PRODUCT DESCRIPTION

It is an acrylic copolymer-based surface leveling putty developed for use on interior facades.

PRODUCT FEATURES

It can be used instead of satin plaster and glutolin putty. Easy application
Long lasting Breathable
Fast drying Odorless
Water and moisture resistant

AREA OF USE

It can be used on interior facades; on all surfaces such as concrete, mineral plaster, rough surfaces, shrinkage cracks.

APPLICATION

Surface Preparation:

All kinds of dirt, oil, dust and loose material should be removed from the application surface, and primed with Ado-binder or Izolin acrylic primer.

Application: It should be applied with trowel in 1 or 2 coats depending on the porosity of the surface. It can be sanded after 24 hours. It is recommended that the newly applied surface be protected from direct sunlight and abundant breeze.

TECHNICAL SPECIFICATIONS

Resin type	Acrylic copolymer	Drying Times (at 23 ± 2°C and 50% relative humidity)	
Color	Yellowish	Touch Dry	2-4 hours
Gloss	Matt	Dust dry	4-5 hours
Viscosity (cPoises at 25°C)	1000 ± 50	Hard dry	24 hours
Density (g/cm ³ , 20°C)	1.80 g/cm ³		
Solid Matter	72 ± 2 g/cm		

PAINTED AREA - CONSUMPTION

In a single coat, depending on the surface;
20-25 m² surface can be primed with 25 Kg.

*A controlled sample run should be performed to estimate the precise consumption.

STORAGE AND PACKAGING INFORMATION

Packaging Information: Packaging Information: 25 Kg

Storage Conditions: It can be stored for 3 years in its unopened package in a cool and dry environment at a temperature of 5 to 35°C, protecting from frost and direct sunlight.

HEALTH AND SAFETY INFORMATION

Pay attention to the health and safety statements on the product packaging. The rules specified in the product safety data sheet must be observed. Contact your nearest health care provider in case of unexpected health problems.