

## ALUMINUM GILDING PAINT

**PRODUCT DESCRIPTION** Hydrocarbon resin based, fast-drying metal parts paint combined with aluminum pigment.

**PRODUCT FEATURES**

- 350°C temperature resistance
- Ready-to-use.
- Matt appearance
- Metallic appearance
- Fast drying
- Easy application

**AREA OF USE** It can be used safely on all kinds of metal surfaces, stoves, chimneys, exhaust pipes.

**RECOMENDED APPLICATION**

**Surface Preparation:** All kinds of dirt, oil, dust should be removed from the application surface.  
**Application:** Adolin Aluminum Gilding is ready to use. It should be thoroughly mixed and applied with brush or spray gun.

**TECHNICAL INFORMATIONS**

TECHNICAL SPECIFICATIONS	
Resin type	Hydrocarbon resin
Color	Aluminum
Gloss	Semi - Gloss
Gloss (60°C)	45 - 50 Gloss
Viscosity (25°C)	135 ± 2 KU
Density (20°C)	1,15 ± 0,05 g/cm
Solid matter	70 ± 2 g/cm
Flas Point	21°C

DRYING TIMES	
Touch Dry	10 - 15 min
Recoating tme	1 hours
Dust Dry	15 min.
Hard dry	3-4 hours

**PAINTED AREA CONSUMPTION**

Wet film thicknes	: 75 -80	*A controlled sample run should be performed to estimate the precise consumption.
Dry film thicknes	: 45-50	
Consumption (m <sup>2</sup> /L)	: 11 - 12	
Consumption (m <sup>2</sup> /Kg)	: 11 - 12	

**STORAGE AND PACKAGING INFORMATION**

Packaging Information: 0.09 Liter, 0.2 Liter, 0.375 Liter, 0.7 Liter, 2.5 Liter, 12 Liter, 15 L  
 Storage Conditions: It can be stored for 3 years in its unopened package in a cool and dry environment at a temperature of 5 to 35°C, protecting from frost and direct sunlight.

**HEALTH AND SAFETY INFORMATION**

Pay attention to the health and safety statements on the product packaging. The rules specified in the product safety data sheet must be observed. Contact your nearest health care provider in case of unexpected health problems.