

COOPER GILDING PAINT

PRODUCT DESCRIPTION

Hydrocarbon resin based, fast-drying metal parts paint combined with copper pigment.

PRODUCT FEATURES

- 250°C temperature resistance
- Ready-to-use.
- Fast Drying
- Easy Application

AREA OF USE

It can be used safely on all kinds of metal surfaces, stoves, chimneys, exhaust pipes.

RECOMENDED APPLICATION

Surface Preparation: All kinds of dirt, oil, dust should be removed from the application surface.

Application: Adolin Cooper Gilding is ready to use. It should be thoroughly mixed and applied with brush or spray gun.

TECHNICAL INFORMATIONS

TECHNICAL SPECIFICATIONS

Resin type	Hydrocarbon resin
Color	Gold
Gloss	Semi Gloss
Gloss (60°C)	45 - 50 Gloss
Viscosity (25°C)	Luquid fluid
Density (20°C)	1,15 ± 0,05 g/cm
Solid matter	60 ± 2 g/cm
Flash Point	21°C

DRYING TIMES

Touch Dry	10 -15 min
Recoating tme	1 hours
Dust Dry	15 min.
Hard dry	3-4 hours

PAINTED AREA CONSUMPTION

Wet film thicknes	: 75 -80
Dry film thicknes	: 45-50
Consumption (m ² /L)	: 11 - 12
Consumption (m ² /Kg)	: 11 - 12

*A controlled sample run should be performed to estimate the precise consumption.

STORAGE AND PACKAGING INFORMATION

Packaging Information: 0.09 Liter, 0.2 Liter, 0.375 Liter, 0.7 Liter, 2.5 Liter, 12 Liter, 15 L
Storage Conditions: It can be stored for 3 years in its unopened package in a cool and dry environment at a temperature of 5 to 35°C, protecting from frost and direct sunlight.

HEALTH AND SAFETY INFORMATION

Pay attention to the health and safety statements on the product packaging. The rules specified in the product safety data sheet must be observed. Contact your nearest health care provider in case of unexpected health problems.