

**TENNIS COURT PAINT****PRODUCT DESCRIPTION**

Water-based, acrylic copolymer-based matt top coat tennis court paint..

PRODUCT FEATURES

- Excellent adhesion
- Resistant to adverse weather conditions
- Flexible structure
- Non-fading and non-cracking
- High Coverage

AREA OF USE

It can be used safely on tennis courts, asphalt and curbstones.

RECOMENDED APPLICATION**Surface Preparation:**

The application surface must be free from dust, dirt, grease, oil etc. and care should be taken to ensure that the surface is dry before application. The surface should be primed with Izolin 1/7 concentrate primer and the top coat should be applied after 8 hours.

Application:

Adolin Tennis Court Paint should be applied in 2 coats with brush and roller. The first coat should be applied by thinning 10% and after 6 hours the second coat should be applied without thinning. 24 hours should be allowed for full drying before the application field comes into operation.

TECHNICAL INFORMATION**TECHNICAL SPECIFICATIONS**

Resin type	Acrylic copolymer
Color	Gren, Red, White
Gloss	Matt
Viscosity (25°C)	350 ± 5 g/cm ³
Density (20°C)	1,20 ± 2 g/cm
Solid matter	51 ± 2 g/cm

DRYING TIMES

Touch Dry	1 hours
Recoating tme	4 hours
Dust Dry	2 hours
Hard dry	24 hours

PAINTED AREA CONSUMPTION

Wet film thickness (microns): 150

Dry film thickness (microns) : 100

Consumption (m²/L) : 6-7

Consumption (m²/Kg) : 2-3

*A controlled sample run should be performed to estimate the precise consumption.

STORAGE AND PACKAGING INFORMATION

Packaging Information:15 Kg

Storage Conditions: It can be stored for 3 years in its unopened package in a cool and dry environment at a temperature of 5 to 35°C, protecting from frost and direct sunlight.

HEALTH AND SAFETY INFORMATION

Pay attention to the health and safety statements on the product packaging. The rules specified in the product safety data sheet must be observed. Contact your nearest health care provider in case of unexpected health problems