

DECOFER

PRODUCT DESCRIPTION Alkyd resin based, metallic and glossy top coat paint resistant to sun rays and environmental factors.

PRODUCT FEATURES

- High UV resistance
- Fast drying
- Excellent adhesion
- Metallic appearance
- Easy application
- Suitable for interior and exterior use
- Long lasting
- Resistant to scratch and impact

AREA OF USE

It is used to give protective and decorative appearance on all kinds of metal, wood, wrought iron surfaces.

RECOMENDED APPLICATION

Surface Preparation:

The application surface should be cleaned from all kinds of dirt, oil, dust and loose coatings, and necessary surface correction procedures should be completed. The surface should be lightly sanded and cleaned from dust

Application: It should be thinned with industrial thinner 15-20% by volume and applied using a brush or roller Dilute with 15% and apply by brush or roller. It should not be applied on synthetic painted surfaces.

TECHNICAL INFORMATION

TECHNICAL SPECIFICATIONS

Resin type	Alkyd
Color	Gold, Cooper, Silver
Gloss	Glossy
Glossy	85 ± 5 Gloss
Viscosity (25°C)	95 ± 2 KU
Density (20°C)	1,05 ± 0,05 g/cm
Solid matter	60 ± 2 g/cm
Flas Point	21°C

DRYING TIMES

Touch Dry	30-40 min
Recoating tme	2-3 hours
Dust Dry	15 min.
Hard dry	12 hours

PAINTED AREA CONSUMPTION

Wet film thicknes	: 75 -80
Dry film thicknes	: 45-50
Consumption (m ² /L)	: 12-14
Consumption (m ² /Kg)	: 10- 12

*A controlled sample run should be performed to estimate the precise consumption.

STORAGE AND PACKAGING INFORMATION

Packaging Information: 0.20 L, 0.375 L, 0.75 L, 2.5 L, 12 Kg
Storage Conditions: It can be stored for 3 years in its unopened package in a cool and dry environment at a temperature of 5 to 35°C, protecting from frost and direct sunlight.

HEALTH AND SAFETY INFORMATION

Pay attention to the health and safety statements on the product packaging. The rules specified in the product safety data sheet must be observed. Contact your nearest health care provider in case of unexpected health problems.