

HAMMERTON PAINT

PRODUCT DESCRIPTION Adolin Hammerton paint is a styrene-modified alkyd resin-based, air drying, fast drying top coat paint with hammered metal appearance.

- PRODUCT FEATURES**
- Fast drying
 - Extra glossy
 - High UV resistance
 - Direct application on metal
 - Excelent adhesion
 - Resistant to physical effects and impacts
 - Flexible structure
 - Resistant to adverse weather conditions

AREA OF USE It can be used safely for painting of machinery, agricultural, home, garden tools, on surfaces such as , tractor, trailer, auto radiator components, on all kinds of metal parts such as barrels, valves, steel cupboards and steel tables.

RECOMENDED APPLICATION

Surface Preparation: Before application, the surface should be cleaned from dust, rust, grease and oil, and should be sanded at least at grade ST2.
Application:Hammerton Paint is ready to use. It should be applied from a distance of 35-40 cm with spray gun angle of 40° to 80° and at a pressure of 3-4 atm.

| TECHNICAL INFORMATION | TECHNICAL SPECIFICATIONS | | DRYING TIMES | |
|-----------------------|--------------------------|-------|---------------|-----------|
| | Resin type | Alkyd | | Touch Dry |
| Color | Hammerton color card | | Recoating tme | 1-2 hours |
| Gloss | Glossy | | Dust Dry | 20 min. |
| Gloss (60°C) | 90 | | Hard dry | 2-3 hours |
| Viscosity (25°C) | 78 ± 2 KU | | | |
| Density (20°C) | 1,20 ± 0.05 g/ml (White) | | | |
| Solid matter | 51 ± 2 (by weight) | | | |
| Flash Point | 21°C | | | |

PAINTED AREA CONSUMPTION

Wet film thicknes : 75 - 80
 Dry film thicknes : 45 - 50
 Consumption (m² /L) : 8 -9
 Consumption (m² /Kg) : 9 - 10

STORAGE AND PACKAGING INFORMATION

Packaging Information: 0,75 Liter, 2,5 Liter, 15 Liter
 Storage Conditions: It can be stored for 3 years in its unopened package in a cool and dry environment at a temperature of 5 to 35°C, protecting from frost and direct sunlight.

HEALTH AND SAFETY INFORMATION

Pay attention to the warnings indicated in the precautionary statements of hazards and safety precautions on the product packaging.
 The rules specified in the product safety data sheet must be observed.
 Contact your nearest health care provider in case of unexpected health problems.