

## INDUSTRIAL PAINT

### PRODUCT DESCRIPTION

Adolin Industrial Paint is a styrene alkyd resin-based, air drying top coat paint.

### PRODUCT FEATURES

- Fast drying
- Semi-matt
- Long lasting
- High Coverage
- Excelent adhesion
- Resistant to physical effects and impacts
- Flexible structure
- Resistant to adverse weather conditions

### AREA OF USE

It can be used safely for painting of machinery, agricultural, home, garden tools, on surfaces such as , tractor, trailer, auto radiator components, on all kinds of metal parts such as barrels, valves, steel cupboards and steel tables.

### RECOMENDED APPLICATION

**Surface Preparation:** Before application, the surface should be cleaned from dust, rust, grease and oil, should be sanded at least at ST2 and primed with Adolin Rapid Primer. After primer application, 12 hours should be allowed to dry.

**Application:** Adolin Industrial Paint should be thinned by 20-25% with industrial thinner and should be applied with spray gun angle of 40° to 80°. Second coat application is recommended to be done after 2-3 hours.

### TECHNICAL INFORMATIONS

#### TECHNICAL SPECIFICATIONS

Resin type	Alkyd
Color	Colors of the color card
Gloss	Semi Gloss
Gloss (60°C)	55
Viscosity (25°C)	100 ± 5 KU
Density (20°C)	1,40 ± 0.05 g/ml (White)
Solid matter	65 ± 2 (by weight)
Flash Point	21°C

#### DRYING TIMES

Touch Dry	20 min.
Recoating tme	1-2 hours
Dust Dry	1 hours
Hard dry	2-3 hours

### PAINTED AREA CONSUMPTION

Wet film thicknes	: 75 - 80
Dry film thicknes	: 45 - 50
Consumption (m <sup>2</sup> /L)	: 10 - 12
Consumption (m <sup>2</sup> /Kg)	: 8 - 9

### STORAGE AND PACKAGING INFORMATION

Packaging Information: 0,75 Kg, 2,5 Kg, 15 Kg  
 Storage Conditions: It can be stored for 3 years in its unopened package in a cool and dry environment at a temperature of 5 to 35°C, protecting from frost and direct sunlight.

### HEALTH AND SAFETY INFORMATION

Pay attention to the warnings indicated in the precautionary statements of hazards and safety precautions on the product packaging.  
 The rules specified in the product safety data sheet must be observed.  
 Contact your nearest health care provider in case of unexpected health problems.