

**RAPID INDUSTRIAL PAINT**

**PRODUCT DESCRIPTION** Adolin Rapid Industrial Paint is a styrene alkyd resin-based, air drying, glossy top coat paint.

- PRODUCT FEATURES**
- Flexible structure
  - High water tightness
  - Excellent adhesion
  - High abrasion resistance
  - Excelent adhesion
  - Resistant to physical effects and impacts
  - Flexible structure
  - Resistant to adverse weather conditions

**AREA OF USE** It can be used safely for painting of machinery, agricultural, home, garden tools, on surfaces such as , tractor, trailer, auto radiator components, on all kinds of metal parts such as barrels, valves, steel cupboards and steel tables.

**RECOMENDED APPLICATION**

**Surface Preparation:** Before application, the surface should be cleaned from dust, rust, grease and oil, should be sanded at least at ST2 and primed with Adolin Rapid Primer. After primer application, 12 hours should be allowed to dry.

**Application:** Adolin Rapid Industrial Paint should be thinned by 20-25% with industrial thinner and should be applied with spray gun angle of 40° to 80°.. Second coat application is recommended to be done after 1-2 hours.

TECHNICAL INFORMATION	TECHNICAL SPECIFICATIONS		DRYING TIMES	
	Resin type	Alkyd	Touch Dry	20 min.
Color	Colors of the color card	Recoating tme	1-2 hours	
Gloss	Glossy	Dust Dry	40 min.	
Gloss (60°C)	90	Hard dry	2-3 hours	
Viscosity (25°C)	100 ± 5 KU			
Density (20°C)	1,25 ± 0.05 g/ml (White)			
Solid matter	65 ± 2 (by weight)			
Flash Point	21°C			

**PAINTED AREA CONSUMPTION**

Wet film thicknes : 75 -80  
 Dry film thicknes : 45-50  
 Consumption (m<sup>2</sup> /L) : 12-14  
 Consumption (m<sup>2</sup> /Kg) : 10- 12

**STORAGE AND PACKAGING INFORMATION**

Packaging Information: 0,75 Liter, 2,5 Liter, 15 Kg  
 Storage Conditions: It can be stored for 3 years in its unopened package in a cool and dry environment at a temperature of 5 to 35°C, protecting from frost and direct sunlight.

**HEALTH AND SAFETY INFORMATION**

Pay attention to the warnings indicated in the precautionary statements of hazards and safety precautions on the product packaging.  
 The rules specified in the product safety data sheet must be observed.  
 Contact your nearest health care provider in case of unexpected health problems.