

**AQUATUT - Acrylic Waterproofing Coating****PRODUCT DESCRIPTION**

Elastomeric acrylic resin-based, up to 7-fold flexible acrylic waterproofing coating.

**PRODUCT FEATURES**

- Waterproof
- Long lasting
- Ultra-flexible
- Four-season application
- Easy application
- It can be colored
- Excellent adhesion
- Odorless.

**AREA OF USE**

It can be used safely on interior and exterior facades where waterproofing and moisture impermeability is desired, such as concrete, brick, china, plaster, ytong, briquette, galvanized sheet, roof coverings, cistern, channel, horizontal and vertical surfaces and wall and window door moldings.

**RECOMENDED APPLICATION****Surface Preparation:**

The application surface should be cleaned from all kinds of dirt, grease, oil, dust and loose material. In floor applications, care should be taken to ensure that the floor is sloped. The primer prepared with 1 part Aquatut and 1 part water should be applied to the surface and 12 hours should be allowed to dry.

**Application:**

Aquatut waterproofing coating should be applied in 2 coats without thinning and with 24-hour interval. If a ceramic tile-like process is to be performed, it should be done after 24 hours

**TECHNICAL INFORMATION****TECHNICAL SPECIFICATIONS**

Resin type	Elastomeric Acrylic
Color	White
Gloss	Semi matt
Viscosity (25°C)	500 ± 25 g/cm <sup>3</sup>
Density (20°C)	1,34 ± 2 g/cm
Solid matter	75 ± 2 g/cm

**DRYING TIMES**

Touch Dry	6 hours
Recoating tme	12 hours
Dust Dry	24 hours
Hard dry	48 hours

**PAINTED AREA CONSUMPTION**

In a single coat, depending on the surface;  
1.5 m<sup>2</sup> surface can be coated with 1 Kg.  
4 m<sup>2</sup> surface can be coated with 3.5 Kg.  
15 m<sup>2</sup> surface can be coated with 10 Kg.  
30 m<sup>2</sup> surface can be coated with 20 Kg.

\*A controlled sample run should be performed to estimate the precise consumption.

**STORAGE AND PACKAGING INFORMATION**

Packaging Information: 1 Kg, 3.5 Kg, 10 Kg, 20 Kg  
Storage Conditions: It can be stored for 3 years in its unopened package in a cool and dry environment at a temperature of 5 to 35°C, protecting from frost and direct sunlight.

**HEALTH AND SAFETY INFORMATION**

Pay attention to the health and safety statements on the product packaging. The rules specified in the product safety data sheet must be observed. Contact your nearest health care provider in case of unexpected health problems