

COLD ROAD MARKING PAINT

PRODUCT DESCRIPTION

Alkyd resin-based, one-component, solvent-based cold road marking paint.

PRODUCT FEATURES

- High adhesion strength
- High UV resistance
- Fast drying
- Resistant to yellowing
- Easy application
- Impact resistant
- Sealing structure

AREA OF USE

It can be used safely on highways, concrete, asphalt, mosaic, curbstones and factory floors and for all kinds of marking.

APPLICATION

Surface Preparation: The application surface should be cleaned from all kinds of dirt, oil, dust and loose coatings, and necessary surface correction procedures should be completed. The best result is achieved on asphalt surfaces and it is not recommended for application on vacuum concrete surfaces as adhesion will be weak. **Application:** For applications with a brush and roller, it should be applied without thinning, in two coats with 15 minutes apart. For applications with a spray gun, it should be applied after thinning 5-8% with road marking thinner. If desired, the glass beads can be sprayed before drying starts.

TECHNICAL SPECIFICATIONS

| TECHNICAL SPECIFICATIONS | | Drying Times | |
|--------------------------|---------------------|--|------------|
| Resin type | Alkyd | Touch dry | 10 min |
| Color | White,yellow,red | Dust dry | 15 min |
| Gloss | Mat | Recoating time | 15 min |
| Gloss (60°C) | 4-6 Gloss | Hard dry | 15-20 min. |
| Solid matter | 75 ± 2 (by weight) | | |
| Viscosity (25°C, KU) | 90 ± 5 g/ml (white) | <small>(at 23 ± 2°C and 50% relative humidity)</small> | |
| Density (g/ml) | 1,55 ± 0,05 (white) | | |
| Flash point | 21°C | | |

PAINTED AREA CONSUMPTION

In a single coat, depending on the type of wood;
 4 m2 surface can be painted with 0.875 Kg.
 12 m2 surface can be painted with 3 Kg.
 80 m2 surface can be painted with 20 Kg.
 100 m2 surface can be painted with 25 Kg.

STORAGE AND PACKAGING INFORMATION

Packaging Information: 0.875 Kg, 3 Kg, 20 Kg, 25 Kg
 Storage Conditions: It can be stored for 3 years in its unopened package in a cool and dry environment at a temperature of 5 to 35°C, protecting from frost and direct sunlight.

HEALTH AND SAFETY INFORMATION

Pay attention to the warnings indicated in the precautionary statements of hazards and safety precautions on the product packaging.
 The rules specified in the product safety data sheet must be observed.
 Contact your nearest health care provider in case of unexpected health problems.