

**ADOLİN SELÜLOZİK BOYA****Safety Data Sheet**

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

**SECTION 1. Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**Product name **ADOLİN SELÜLOZİK BOYA****1.2. Relevant identified uses of the substance or mixture and uses advised against**Intended use **Alkyd resin-based nitrocellulose modified, glossy top coat paint.****1.3. Details of the supplier of the safety data sheet**

Name **ADOLIN BOYA KIMYA SAN VE TIC LIMITED SIRKETI**  
Full address **Fevzipaşa Mh. Erdoğan Sk. 15/A 35520, Silivri**  
District and Country **İSTANBUL (TR)**  
**Türkiye**  
Tel. **+90 212 735 38 24**

**1.4. Emergency telephone number**For urgent inquiries refer to **+90 212 735 38 24****SECTION 2. Hazards identification****2.1. Classification of the substance or mixture**

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2	H225	Highly flammable liquid and vapour.
Reproductive toxicity, category 2	H361d	Suspected of damaging the unborn child.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Specific target organ toxicity - repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.

**2.2. Label elements**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **Danger**

Hazard statements:

<b>H225</b>	Highly flammable liquid and vapour.
<b>H361d</b>	Suspected of damaging the unborn child.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H373</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H315</b>	Causes skin irritation.
<b>H336</b>	May cause drowsiness or dizziness.

**ADOLIN SELÜLOZİK BOYA****SECTION 2. Hazards identification ... / >>**

Precautionary statements:

<b>P210</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
<b>P331</b>	Do NOT induce vomiting.
<b>P280</b>	Wear protective gloves/ protective clothing / eye protection / face protection.
<b>P301+P310</b>	IF SWALLOWED: Immediately call a POISON CENTER / doctor / . . .
<b>P370+P378</b>	In case of fire: use . . . to extinguish.
<b>P261</b>	Avoid breathing dust / fume / gas / mist / vapours / spray.

**Contains:** TOLUENE  
N-BUTYL ACETATE

**2.3. Other hazards**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

**SECTION 3. Composition/information on ingredients****3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
<b>TOLUENE</b>		
INDEX 601-021-00-3	$30 \leq x < 32,5$	<b>Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H336</b>
EC 203-625-9		
CAS 108-88-3		
<b>N-BUTYL ACETATE</b>		
INDEX 607-025-00-1	$1 \leq x < 1,5$	<b>Flam. Liq. 3 H226, STOT SE 3 H336, EUH066</b>
EC 204-658-1		
CAS 123-86-4		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

**SECTION 4. First aid measures****4.1. Description of first aid measures**

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

**SKIN:** Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

**INHALATION:** Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

**INGESTION:** Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

Specific information on symptoms and effects caused by the product are unknown.

**4.3. Indication of any immediate medical attention and special treatment needed**

Information not available

**SECTION 5. Firefighting measures****5.1. Extinguishing media**

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide and chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

## SECTION 5. Firefighting measures ... / >>

### UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water.

Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

### 5.2. Special hazards arising from the substance or mixture

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If large quantities of the product are involved in a fire, they can make it considerably worse. Do not breathe combustion products.

### 5.3. Advice for firefighters

#### GENERAL INFORMATION

In the case of fire, use jets of water to cool the containers to prevent the risk of explosions (product decomposition and excess pressure) and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Remove all containers containing the product from the fire, if it is safe to do so.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage

### 7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised.

### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition.

**ADOLIN SELÜLOZİK BOYA****SECTION 7. Handling and storage ... / >>****7.3. Specific end use(s)**

Information not available

**SECTION 8. Exposure controls/personal protection****8.1. Control parameters**

Regulatory References:

ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
TUR	Türkiye	Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2022

**TOLUENE****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLEP	ITA	192	50			SKIN
ESD	TUR	192	50	384	100	SKIN
WEL	GBR	191	50	384	100	SKIN
OEL	EU	192	50	384	100	SKIN
TLV-ACGIH			20			

**N-BUTYL ACETATE****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLEP	ITA	241	50	723	150	
WEL	GBR	724	150	966	200	
OEL	EU	241	50	723	150	
TLV-ACGIH			50		150	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

**8.2. Exposure controls**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

**HAND PROTECTION**

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

**SKIN PROTECTION**

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

**EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the

**ADOLİN SELÜLOZİK BOYA****SECTION 8. Exposure controls/personal protection ... />>**

threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

**ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

**SECTION 9. Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Properties	Value	Information
Appearance	viscous liquid	
Colour	not available	
Odour	characteristic	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	5,5 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	not available	
Kinematic viscosity	not available	
Solubility	not available	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	1,1-1,3 g/cm <sup>3</sup>	Temperature: 20 °C
Relative vapour density	not available	
Particle characteristics	not applicable	

**9.2. Other information****9.2.1. Information with regard to physical hazard classes**

Information not available

**9.2.2. Other safety characteristics**

Information not available

**SECTION 10. Stability and reactivity****10.1. Reactivity**

The product can decompose and/or react violently.

**TOLUENE**

Avoid exposure to: light.

**N-BUTYL ACETATE**

Decomposes on contact with: water.

**10.2. Chemical stability**

See previous paragraph.

**10.3. Possibility of hazardous reactions**

See paragraph 10.1.

**TOLUENE**

Risk of explosion on contact with: fuming sulphuric acid, nitric acid, silver perchlorate, nitrogen dioxide, non-metal halogenates, acetic acid, organic nitrocompounds. May form explosive mixtures with: air. May react dangerously with: strong oxidising agents, strong

**ADOLIN SELÜLOZİK BOYA****SECTION 10. Stability and reactivity ... / >>**

acids,sulphur.

**N-BUTYL ACETATE**

Risk of explosion on contact with: strong oxidising agents.May react dangerously with: alkaline hydroxides,potassium tert-butoxide.Forms explosive mixtures with: air.

**10.4. Conditions to avoid**

As the product decomposes even at ambient temperature, it must be stored and used at a controlled temperature. Avoid violent blows.

**N-BUTYL ACETATE**

Avoid exposure to: moisture,sources of heat,naked flames.

**10.5. Incompatible materials****N-BUTYL ACETATE**

Incompatible with: water,nitrates,strong oxidants,acids,alkalis,zinc.

**10.6. Hazardous decomposition products**

Information not available

**SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure**TOLUENE**

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

**N-BUTYL ACETATE**

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**TOLUENE**

Toxic effect on the central and peripheral nervous system with encephalopathy and polyneuritis; irritating for the skin, conjunctiva, cornea and respiratory apparatus.

**N-BUTYL ACETATE**

In humans, the substance's vapours cause irritation of the eyes and nose. In the event of repeated exposure, skin irritation, dermatitis (dryness and cracking of the skin) and keratitis appear.

Interactive effects**TOLUENE**

Certain drugs and other industrial products can interfere with the metabolism of the toluene.

**N-BUTYL ACETATE**

A case of acute intoxication been reported involving a 33 year old worker while cleaning a tank with a preparation containing xylenes, butyl acetate and ethylene glycol acetate. The person had irritation of the conjunctiva and upper respiratory tract, drowsiness and motor coordination disorders, which disappeared within 5 hours. The symptoms are attributed to poisoning by mixed xylenes and butyl acetate, with a possible synergistic effect responsible for the neurological effects. Cases of vacuolar keratitis are reported in workers exposed to a mixture of butyl acetate and isobutanol vapours, but with uncertainty concerning the responsibility of a particular solvent (INRC, 2011).

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

Not classified (no significant component)

ATE (Oral) of the mixture:

Not classified (no significant component)

ATE (Dermal) of the mixture:

Not classified (no significant component)

# ADOLIN SELÜLOZİK BOYA

## SECTION 11. Toxicological information ... / >>

TOLUENE  
LD50 (Dermal): 12124 mg/kg Rabbit  
LD50 (Oral): 5580 mg/kg Rat  
LC50 (Inhalation vapours): 28,1 mg/l/4h Rat

N-BUTYL ACETATE  
LD50 (Dermal): > 5000 mg/kg Rabbit  
LD50 (Oral): > 6400 mg/kg Rat  
LC50 (Inhalation vapours): 21,1 mg/l/4h Rat

### SKIN CORROSION / IRRITATION

Causes skin irritation

### SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

### RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

### CARCINOGENICITY

Does not meet the classification criteria for this hazard class

TOLUENE  
Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 1999).  
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

### REPRODUCTIVE TOXICITY

Suspected of damaging the unborn child

### STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

### STOT - REPEATED EXPOSURE

May cause damage to organs

### ASPIRATION HAZARD

Toxic for aspiration

### 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

## SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

### 12.1. Toxicity

Information not available

### 12.2. Persistence and degradability

**ADOLIN SELÜLOZİK BOYA****SECTION 12. Ecological information ... / >>**

TOLUENE  
Solubility in water 100 - 1000 mg/l  
Rapidly degradable

N-BUTYL ACETATE  
Solubility in water 1000 - 10000 mg/l

**12.3. Bioaccumulative potential**

TOLUENE  
Partition coefficient: n-octanol/water 2,73  
BCF 90

N-BUTYL ACETATE  
Partition coefficient: n-octanol/water 2,3  
BCF 15,3

**12.4. Mobility in soil**

N-BUTYL ACETATE  
Partition coefficient: soil/water < 3

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

**12.6. Endocrine disrupting properties**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

**12.7. Other adverse effects**

Information not available

**SECTION 13. Disposal considerations****13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

**CONTAMINATED PACKAGING**

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**SECTION 14. Transport information****14.1. UN number or ID number**

ADR / RID, IMDG, IATA: 1263

**14.2. UN proper shipping name**

ADR / RID: PAINT or PAINT RELATED MATERIAL

IMDG: PAINT or PAINT RELATED MATERIAL

IATA: PAINT or PAINT RELATED MATERIAL

**SECTION 14. Transport information ... / >>**

**14.3. Transport hazard class(es)**

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



**14.4. Packing group**

ADR / RID, IMDG, IATA: III

**14.5. Environmental hazards**

ADR / RID: NO  
 IMDG: NO  
 IATA: NO

**14.6. Special precautions for user**

ADR / RID:	HIN - Kemler: 30	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
	Special provision: 163, 367, 650		
IMDG:	EMS: F-E, S-E	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 220 L	Packaging instructions: 366
	Passengers:	Maximum quantity: 60 L	Packaging instructions: 355
	Special provision:	A3, A72, A192	

**14.7. Maritime transport in bulk according to IMO instruments**

Information not relevant

**SECTION 15. Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 48-75 TOLUENE

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors  
 not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

**ADOLIN SELÜLOZİK BOYA****SECTION 15. Regulatory information ... / >>**

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

**15.2. Chemical safety assessment**

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

**SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Liq. 2</b>	Flammable liquid, category 2
<b>Flam. Liq. 3</b>	Flammable liquid, category 3
<b>Repr. 2</b>	Reproductive toxicity, category 2
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>STOT RE 2</b>	Specific target organ toxicity - repeated exposure, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>H225</b>	Highly flammable liquid and vapour.
<b>H226</b>	Flammable liquid and vapour.
<b>H361d</b>	Suspected of damaging the unborn child.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H373</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H315</b>	Causes skin irritation.
<b>H336</b>	May cause drowsiness or dizziness.
<b>EUH066</b>	Repeated exposure may cause skin dryness or cracking.

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament

**SECTION 16. Other information ... / >>**

9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**Author of the safety data sheet**

Berna Özgül / Adolin Adolin Boya ve Kimya San. ve Tic. LTD Şirketi

**CALCULATION METHODS FOR CLASSIFICATION**

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.